CAMBRID

DYNA-LIFT SERIES WITH MODEL CSW-10AT INDICATOR STANDARD AND LEGAL FOR TRADE **ELECTRONIC LIFT TRUCK SCALE SYSTEMS**



Dyna-Lift Series Standard Features:

- Two Environmentally Sealed Load Cells
- Large Viewing Port
- Rugged, Solid, Plate Steel Construction
- Urethane Enamel Gray Paint
- Hardened Dual Web Stainless Steel Flexures with Integrated Overload and Underload Protection
- Hardened Stainless Steel Flexure Rods
- (12) VDC Operation Standard

Optional Features:

- (24-48) VDC Operation
- WI-CELL®-LT wireless carriage to indicator communication

Approvals:



AM-5812C







Model CSW-10 Indicator COC#: 06-670A1

The Cambridge Model: DL-CSW-10AT Lift Truck Scale System allows lift truck operations to quickly and precisely weigh and record individual lifts. This rugged piece of industrial equipment increases productivity and eliminates down time. There is no more waiting to get to a scale in a remote location. Time is money... streamline your customer's operation and increase efficiency. Just lift and weigh, the operation never stops. Since Cambridge offers both standard and legal for trade systems... we have the scale for the job!



Model CSW-10AT-LFT Indicator viewed from inside Lift Truck



The perfect scale for trucking companies large and small.

Members:

- THE NATIONAL CONFERENCE ON WEIGHTS AND MEASURES
- THE INTERNATIONAL SOCIETY OF WEIGHING AND MEASUREMENT

CAMBRIDGE

DYNA-LIFT SERIES WITH MODEL CSW-10AT INDICATOR STANDARD AND LEGAL FOR TRADE ELECTRONIC LIFT TRUCK SCALE SYSTEMS

Dyna-Lift Series Sizes and Specifications:





Measurement Canada

Model	Capacity	Graduation	Dimensions	Class
DL-CSW-10AT-LFT-5K	5,000 lk	os. 5	30" X 16"	- 11
	5,000 lb	s. 5	36" X 16"	II

Standard (Non-Legal For Trade)

Model	Capacity (Graduation	Dimensions	Class
DL-CSW-10AT-LT-5K	5,000 lbs.	1	30" X 16"	II
	5,000 lbs.	1 -	36" X 16"	11
DL-CSW-10AT-LT-6K	6,000 lbs.	2	40" X 20"	111
DL-CSW-10AT-LT-8K	8,000 lbs.	2	40" X 20"	111
DL-CSW-10AT-LT-10K	10,000 lbs	. 2	40" X 20"	111
DL-CSW-10AT-LT-12K	12,000 lbs	. 5	40" X 25"	IV
DL-CSW-10AT-LT-15K	15,000 lbs	. 5	40" X 25"	IV

Optional Features:

Dyna-Lift Series with CSW-10AT

- WI-CELL®-LT wireless carriage to indicator communication
- WI-FI link: Transmit to customer wireless hub 802.11 B/G
- DC Thermal Tape Printer
- DC Thermal Adhesive Label Printer
- Severe Service Protection Package
- Center Loading Package
- Wet Environment Package NEMA IV Rated
- Non-Standard Widths (Consult Factory)
- 24 VDC 48 VDC Operation with Power Conditioning

SONICH INDUSTRIAL SALES CO., INC.

CLEVELAND, OHIO

(440) 546-1170 Fax (440) 546-9141 www.sonichindustrial.com

Email: sales@sonichindustrial.com

Model CSW-10AT-LT/LFT



Features:

- Accuracy of .1% of the Applied Loads
- Bright 1/2" LED Display
- Zero, Gross, Tare, Net and Print Functions
- RS-232 Port
- On/Off Switch
- Industrial Grade Aluminum, Dust-Tight Enclosure with Swivel Stand
- (12) VDC Operation Standard
- (24-48) VDC Operation Optional
- Weight Totalization
- Front Panel Calibration with Audit Trail

Print Format Samples

Sample Ticket:

Gross(lb): 1200 Tare(lb): 200 Net(lb): 1000

Sample Ticket with Totalization:

Wt# 1 550 Wt# 2 450 Total Wt. 1000 lb

Cambridge Scale Works, Inc. will warrant this product for one full year against defects in material and/or workmanship.